

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier	
Trade name or designation of the mixture	Yamalube 15w-50 Performance (For MC)
Registration number	-
Synonyms	None.
SDS number	A4045
Issue date	22-March-2013
Version number	01
Revision date	-
Supersedes date	-
1.2. Relevant identified uses of t	the substance or mixture and uses advised against
Identified uses	Engine oil.
Uses advised against	None known.

1.3. Details of the supplier of the safety data sheet

Supplier	YAMAHA MOTOR EUROPE N.V.
Address	Koolhovenlaan 101
	1119 NC Schipol-Rijk, The Netherlands
Telephone	+31 (0) 20 654 6000
Fax	+31 (0) 20 654 6888
e-mail	P&Acustomersupport@yamaha-motor.nl
1.4 Emergency telephone number	+31 (0) 20 654 6000

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Directive 67/548/EEC or 1999/45/EC as amended

R52/53

This preparation is classified as dangerous according to Directive 1999/45/EC and its amendments.

Classification

The full text for all R-phrases is displayed in section 16.

Classification according to Regulation (EC) No 1272/2008 as amended

Environmental hazards

Hazardous to the aquatic environment, Category 3 H412 - Harmful to aquatic life with long-term aquatic hazard long lasting effects. Hazard summary **Physical hazards** Not classified for physical hazards. **Health hazards** Not classified for health hazards. **Environmental hazards** Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Specific hazards Vapours may form explosive mixtures with air. The harmful effects may increase in used oil.

Main symptoms Prolonged or repeated contact with used oil may cause serious skin diseases, such as dermatitis.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Hazard pictograms	None.	
Signal word	None.	
Hazard statements	H412 - Harmful to aquatic life with long lasting effects.	
Precautionary statements		
Prevention	P273 - Avoid release to the environment.	
Response	Not available.	
Yamalube 15w-50 Performance (For	MC)	SDS EU

913292 Version No.: 01 Revision date: -Issue date: 22-March-2013 Storage

Not available.

Disposal	P501 - Dispose of contents/container in accordance with local/regional/national/international regulations.			
Supplemental label information				
2.3. Other hazards	Not a PBT or vPvB substance or mixture.			
	This Safety Data Sheet complies with the requirements of Regulation (EC) No 453/2010.			
SECTION 3: Composition/	information on ingredients			
3.2. Mixtures				
General information				
Chemical name	% CAS-No. / EC No. REACH Registration No. INDEX No. Notes			
Lubricating oils	70 - < 80 74869-22-0 - 649-484-00-0 278-012-2			
Classification: DS	D: -			
CL	P: -			
Alkyl phenol	< 1 Unknown			
Classification: DS	D: Xi;R38, N;R50/53			
CL	P: Skin Irrit. 2;H315, Aquatic Acute 1;H400, Aquatic Chronic 1;H410			
DSD: Directive 67/548/EEC. CLP: Regulation No. 1272/20 #: This substance has workpla	ace exposure limit(s).			
Composition comments	The full text for all R- and H-phrases is displayed in section 16. All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. Lubricating oil: Contains less than 3 % DMSO extract as measured by IP 346.			
SECTION 4: First aid meas	sures			
General information	First aid personnel must be aware of own risk during rescue.			
4.1. Description of first aid mean				
Inhalation	Move injured person into fresh air and keep person calm under observation. Get medical attention if any discomfort continues.			
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. Get medical attention promptly if symptoms occur after washing. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital.			
Eye contact	Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyelids wide apart. Get medical attention if irritation develops and persists.			
Ingestion	Rinse mouth thoroughly. Do not induce vomiting. If vomiting occurs, the head should be kept low so that stomach vomit doesn't enter the lungs. Get medical attention.			
4.2. Most important symptoms and effects, both acute and delayed	Prolonged or repeated contact with used oil may cause serious skin diseases, such as dermatitis.			
4.3. Indication of any immediate medical attention and special treatment needed	Treat symptomatically.			
SECTION 5: Firefighting measures				
General fire hazards	Will burn if involved in a fire.			
5.1. Extinguishing media Suitable extinguishing media	Extinguish with foam, carbon dioxide, dry powder or water fog.			
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.			
5.2. Special hazards arising from the substance or mixture	By heating and fire, harmful vapours/gases may be formed.			

5.3. Advice for firefighters	
Special protective equipment for firefighters	Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Special fire fighting procedures	Use standard firefighting procedures and consider the hazards of other involved materials. Move container from fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures		
For non-emergency personnel	Stay upwind. Eliminate all sources of ignition. Avoid inhalation of vapours and spray mists. Avoid prolonged and repeated contact. Avoid contact with used oils. Wear appropriate personal	
-	protective equipment. For personal protection, see section 8 of the SDS.	

For emergency responders Keep unnecessary personnel away.

6.2. Environmental precautions Avoid discharge into drains, water courses or onto the ground. Contact local authorities in case of spillage to drain/aquatic environment.

6.3. Methods and material for containment and cleaning up
 6.4. Reference to other sections
 Remove sources of ignition. Stop the flow of material, if this is without risk. Absorb spillage with non-combustible, absorbent material. In case of spills, beware of slippery floors and surfaces.
 For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling	Provide adequate ventilation. Avoid inhalation of vapours and spray mists. Avoid prolonged and repeated contact. Avoid contact with used oils. Wear appropriate personal protective equipment. Do not eat, drink or smoke when using the product. Observe good industrial hygiene practices.
7.2. Conditions for safe storage, including any incompatibilities	Keep away from heat, sparks and open flame. Keep containers tightly closed in a cool, well-ventilated place.
7.3. Specific end use(s)	Engine oil.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Belgium. Exposure Limit Values.

Components	Туре	Value	Form
Lubricating oils (CAS 74869-22-0)	STEL	10 mg/m3	Mist.
1 1000 22 0)	TWA	5 mg/m3	Mist.

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Туре	Value		
TWA	5 mg/m3		
nent Decree 361			
Туре	Value	Form	
Ceiling	10 mg/m3	Aerosol	
TWA	5 mg/m3	Aerosol	
5			
Туре	Value	Form	
TLV	1 mg/m3	Mist.	
99, as amended)			
Туре	Value	Form	
TWA	5 mg/m3	Mist.	
Chemical Safety of Workplaces			
Туре	Value	Form	
Ceiling	5 mg/m3	Mist.	
	TWA nent Decree 361 Type Ceiling TWA TWA TWA TWA TWA TUA S Type TLV 99, as amended) Type TWA Chemical Safety of Workplaces Type	TWA5 mg/m3nent Decree 361ValueTypeValueCeiling10 mg/m3TWA5 mg/m3TWA5 mg/m3TypeValueTLV1 mg/m329, as amended)ValueTWA5 mg/m3Chemical Safety of WorkplacesValueTypeValueValue5 mg/m3	TWA5 mg/m3nent Decree 361YalueFormTypeValueFormCeiling10 mg/m3AerosolTWA5 mg/m3AerosolTWA5 mg/m3MerosolTUA5 mg/m3Mist.TypeValueFormTLV1 mg/m3Mist.99, as amended)FormTypeValueFormTWA5 mg/m3Mist.Chemical Safety of WorkplacesTypeValueForm

913292 Version No.: 01 Revision date: - Issue date: 22-March-2013

Iceland. OELs. Regulation 154/1999 on occupational exposure limits

Components	Туре	Value	Form
∟ubricating oils (CAS 74869-22-0)	TWA	1 mg/m3	Mist.
reland. Occupational Exposure	Limits		
Components	Туре	Value	Form
ubricating oils (CAS 74869-22-0)	TWA	0,2 mg/m3	Inhalable fraction.
taly. OELs			
Components	Туре	Value	Form
ubricating oils (CAS 4869-22-0)	TWA	5 mg/m3	Inhalable fraction.
ithuania. OELs. Limit Values for	or Chemical Substances, Gener	al Requirements (Hygiene No	orm HN 23:2007)
Components	Туре	Value	Form
_ubricating oils (CAS	STEL	3 mg/m3	Fume and mist.
74869-22-0)	TWA	1 mg/m3	Fume and mist.
Netherlands. OELs (binding)			
Components	Туре	Value	Form
ubricating oils (CAS 74869-22-0)	TWA	5 mg/m3	Mist.
•	for Contaminants in the Workpla	ace	
Components	Туре	Value	Form
	TLV	1 mg/m3	Mist.
Lubricating oils (CAS 74869-22-0) Poland. MACs. Minister of Labo			
74869-22-0)	TLV		
74869-22-0) Poland. MACs. Minister of Labo Norking Environment	TLV		
74869-22-0) Poland. MACs. Minister of Labor Norking Environment Components Lubricating oils (CAS	TLV ur and Social Policy Regarding	Maximum Allowable Concent	rations and Intensities in
74869-22-0) Poland. MACs. Minister of Labor Norking Environment Components Lubricating oils (CAS	TLV ur and Social Policy Regarding Type	Maximum Allowable Concent Value 10 mg/m3	trations and Intensities in Form
74869-22-0) Poland. MACs. Minister of Labor Norking Environment Components Lubricating oils (CAS 74869-22-0)	TLV ur and Social Policy Regarding Type STEL	Maximum Allowable Concent Value 10 mg/m3 5 mg/m3	Form Aerosol
24869-22-0) Poland. MACs. Minister of Labor Norking Environment Components Jubricating oils (CAS 24869-22-0) Portugal. VLEs. Norm on occupa	TLV ur and Social Policy Regarding Type STEL TWA ational exposure to chemical ag	Maximum Allowable Concent Value 10 mg/m3 5 mg/m3 gents (NP 1796)	Form Aerosol Aerosol
74869-22-0) Poland. MACs. Minister of Labor Norking Environment Components Lubricating oils (CAS 74869-22-0) Portugal. VLEs. Norm on occupa Components	TLV ur and Social Policy Regarding Type STEL TWA	Maximum Allowable Concent Value 10 mg/m3 5 mg/m3	Form Aerosol
74869-22-0) Poland. MACs. Minister of Labor Working Environment Components Lubricating oils (CAS 74869-22-0)	TLV ur and Social Policy Regarding Type STEL TWA ational exposure to chemical ag Type STEL	Maximum Allowable Concent Value 10 mg/m3 5 mg/m3 gents (NP 1796) Value 10 mg/m3	trations and Intensities in Form Aerosol Aerosol Form Aerosol
24869-22-0) Poland. MACs. Minister of Labor Norking Environment Components Lubricating oils (CAS 24869-22-0) Portugal. VLEs. Norm on occupa Components Lubricating oils (CAS 24869-22-0)	TLV ur and Social Policy Regarding Type STEL TWA ational exposure to chemical ag Type STEL TWA	Maximum Allowable Concent Value 10 mg/m3 5 mg/m3 gents (NP 1796) Value 10 mg/m3 5 mg/m3	Trations and Intensities in Form Aerosol Aerosol Form
74869-22-0) Poland. MACs. Minister of Labor Norking Environment Components -ubricating oils (CAS 74869-22-0) Portugal. VLEs. Norm on occupa Components -ubricating oils (CAS 74869-22-0) Portugal. VLEs. Norm on occupa Components -ubricating oils (CAS 74869-22-0) Romania. OELs. Protection of w	TLV ur and Social Policy Regarding Type STEL TWA ational exposure to chemical ag Type STEL TWA vorkers from exposure to chemic	Maximum Allowable Concent Value 10 mg/m3 5 mg/m3 gents (NP 1796) Value 10 mg/m3 5 mg/m3	trations and Intensities in Form Aerosol Aerosol Form Aerosol
74869-22-0) Poland. MACs. Minister of Labor Norking Environment Components -ubricating oils (CAS 74869-22-0) Portugal. VLEs. Norm on occupa Components -ubricating oils (CAS 74869-22-0) Romania. OELs. Protection of w Components	TLV ur and Social Policy Regarding Type STEL TWA ational exposure to chemical ag Type STEL TWA vorkers from exposure to chemic Type	Maximum Allowable Concent Value 10 mg/m3 5 mg/m3 gents (NP 1796) Value 10 mg/m3 5 mg/m3 cal agents at the workplace Value	trations and Intensities in Form Aerosol Aerosol Form Aerosol
74869-22-0) Poland. MACs. Minister of Labor Norking Environment Components Lubricating oils (CAS 74869-22-0) Portugal. VLEs. Norm on occupa Lubricating oils (CAS 74869-22-0) Romania. OELs. Protection of w Components Lubricating oils (CAS	TLV ur and Social Policy Regarding Type STEL TWA ational exposure to chemical ag Type STEL TWA vorkers from exposure to chemic	Maximum Allowable Concent Value 10 mg/m3 5 mg/m3 gents (NP 1796) Value 10 mg/m3 5 mg/m3 cal agents at the workplace	trations and Intensities in Form Aerosol Aerosol Form Aerosol
74869-22-0) Poland. MACs. Minister of Labor Norking Environment Components Lubricating oils (CAS 74869-22-0) Portugal. VLEs. Norm on occupa Lubricating oils (CAS 74869-22-0) Romania. OELs. Protection of w Components Lubricating oils (CAS	TLV ur and Social Policy Regarding Type STEL TWA ational exposure to chemical ag Type STEL TWA vorkers from exposure to chemic Type	Maximum Allowable Concent Value 10 mg/m3 5 mg/m3 gents (NP 1796) Value 10 mg/m3 5 mg/m3 cal agents at the workplace Value	trations and Intensities in Form Aerosol Aerosol Form Aerosol
74869-22-0) Poland. MACs. Minister of Labor Working Environment Components Lubricating oils (CAS 74869-22-0) Portugal. VLEs. Norm on occupa Components Lubricating oils (CAS 74869-22-0) Romania. OELs. Protection of w Components Lubricating oils (CAS 74869-22-0)	TLV ur and Social Policy Regarding Type STEL TWA ational exposure to chemical ag Type STEL TWA vorkers from exposure to chemic Type STEL	Maximum Allowable Concent Value 10 mg/m3 5 mg/m3 gents (NP 1796) Value 10 mg/m3 5 mg/m3 cal agents at the workplace Value 10 mg/m3 5 mg/m3	Trations and Intensities in Form Aerosol Aerosol Form Aerosol Aerosol
74869-22-0) Poland. MACs. Minister of Labor Norking Environment Components Lubricating oils (CAS 74869-22-0) Portugal. VLEs. Norm on occupa Components Lubricating oils (CAS 74869-22-0) Romania. OELs. Protection of w Components Lubricating oils (CAS 74869-22-0) Romania. OELs. Protection of w Components Lubricating oils (CAS 74869-22-0) Slovakia. OELs. Decree of the gragents	TLV ur and Social Policy Regarding Type STEL TWA ational exposure to chemical ag Type STEL TWA vorkers from exposure to chemic Type STEL TWA vorkers from exposure to chemic	Maximum Allowable Concent Value 10 mg/m3 5 mg/m3 gents (NP 1796) Value 10 mg/m3 5 mg/m3 cal agents at the workplace Value 10 mg/m3 5 mg/m3	Trations and Intensities in Form Aerosol Aerosol Form Aerosol Aerosol
74869-22-0) Poland. MACs. Minister of Labor Norking Environment Components -ubricating oils (CAS 74869-22-0) Portugal. VLEs. Norm on occupa Components -ubricating oils (CAS 74869-22-0) Romania. OELs. Norm on occupa -ubricating oils (CAS 74869-22-0) Romania. OELs. Protection of w Components -ubricating oils (CAS 74869-22-0) Slovakia. OELs. Decree of the gragents Components -ubricating oils (CAS 74869-22-0)	TLV ur and Social Policy Regarding Type STEL TWA ational exposure to chemical ag Type STEL TWA vorkers from exposure to chemic Type STEL TWA vorkers from exposure to chemic Type STEL TWA	Maximum Allowable Concent Value 10 mg/m3 5 mg/m3 gents (NP 1796) Value 10 mg/m3 5 mg/m3 cal agents at the workplace Value 10 mg/m3 5 mg/m3 blic concerning protection of l	Trations and Intensities in Form Aerosol Form Aerosol Aerosol Aerosol
74869-22-0) Poland. MACs. Minister of Labor Norking Environment Components -ubricating oils (CAS 74869-22-0) Portugal. VLEs. Norm on occupa Components -ubricating oils (CAS 74869-22-0) Romania. OELs. Norm on occupa -ubricating oils (CAS 74869-22-0) Romania. OELs. Protection of w Components -ubricating oils (CAS 74869-22-0) Slovakia. OELs. Decree of the gragents Components -ubricating oils (CAS 74869-22-0)	TLV ur and Social Policy Regarding Type STEL TWA ational exposure to chemical ag Type STEL TWA vorkers from exposure to chemic Type STEL TWA overnment of the Slovak Repub Type	Maximum Allowable Concent Value 10 mg/m3 5 mg/m3 gents (NP 1796) Value 10 mg/m3 5 mg/m3 cal agents at the workplace Value 10 mg/m3 5 mg/m3 olic concerning protection of I Value 1 mg/m3	Trations and Intensities in Form Aerosol Form Aerosol Aerosol Aerosol Aerosol Form
74869-22-0) Poland. MACs. Minister of Labor Norking Environment Components Lubricating oils (CAS 74869-22-0) Portugal. VLEs. Norm on occupa Components Lubricating oils (CAS 74869-22-0) Romania. OELs. Protection of w Components Lubricating oils (CAS 74869-22-0) Slovakia. OELs. Decree of the gragents Components Lubricating oils (CAS 74869-22-0) Slovakia. OELs. Decree of the gragents Lubricating oils (CAS 74869-22-0)	TLV ur and Social Policy Regarding Type STEL TWA ational exposure to chemical ag Type STEL TWA vorkers from exposure to chemic Type STEL TWA overnment of the Slovak Repub Type TWA	Maximum Allowable Concent Value 10 mg/m3 5 mg/m3 gents (NP 1796) Value 10 mg/m3 5 mg/m3 cal agents at the workplace Value 10 mg/m3 5 mg/m3 olic concerning protection of I Value	The and mist.
74869-22-0) Poland. MACs. Minister of Labor Working Environment Components Lubricating oils (CAS 74869-22-0) Portugal. VLEs. Norm on occupa Components Lubricating oils (CAS 74869-22-0) Romania. OELs. Norection of w Components Lubricating oils (CAS 74869-22-0) Romania. OELs. Protection of w Components Lubricating oils (CAS 74869-22-0) Slovakia. OELs. Decree of the gragents Components Lubricating oils (CAS 74869-22-0) Slovakia. OELs. Decree of the gragents Components Lubricating oils (CAS 74869-22-0) Spain. Occupational Exposure L	TLV ur and Social Policy Regarding Type STEL TWA ational exposure to chemical ag Type STEL TWA vorkers from exposure to chemic Type STEL TWA overnment of the Slovak Repub Type TWA Limits	Maximum Allowable Concent Value 10 mg/m3 5 mg/m3 gents (NP 1796) Value 10 mg/m3 5 mg/m3 cal agents at the workplace Value 10 mg/m3 5 mg/m3 stic concerning protection of I Value 1 mg/m3 5 mg/m3	The and mist.
74869-22-0) Poland. MACs. Minister of Labor Norking Environment Components Lubricating oils (CAS 74869-22-0) Portugal. VLEs. Norm on occupa Components Lubricating oils (CAS 74869-22-0) Romania. OELs. Nortection of w Components Lubricating oils (CAS 74869-22-0) Romania. OELs. Protection of w Components Lubricating oils (CAS 74869-22-0) Slovakia. OELs. Decree of the gragents Components Lubricating oils (CAS 74869-22-0) Spain. Occupational Exposure L Components Lubricating oils (CAS 74869-22-0)	TLV ur and Social Policy Regarding Type STEL TWA ational exposure to chemical ag Type STEL TWA vorkers from exposure to chemic Type STEL TWA overnment of the Slovak Repub Type TWA	Maximum Allowable Concent Value 10 mg/m3 5 mg/m3 gents (NP 1796) Value 10 mg/m3 5 mg/m3 cal agents at the workplace Value 10 mg/m3 5 mg/m3 olic concerning protection of I Value 1 mg/m3 5 ppm Value	trations and Intensities in Form Aerosol Form Aerosol Aerosol Aerosol Aerosol Form Aerosol Form Funce and mist. Fume and mist. Form
74869-22-0) Poland. MACs. Minister of Labor Norking Environment Components Lubricating oils (CAS 74869-22-0) Portugal. VLEs. Norm on occupa Components Lubricating oils (CAS 74869-22-0) Romania. OELs. Protection of w Components Lubricating oils (CAS 74869-22-0) Slovakia. OELs. Decree of the gragents Components Lubricating oils (CAS 74869-22-0) Slovakia. OELs. Decree of the gragents Lubricating oils (CAS 74869-22-0)	TLV ur and Social Policy Regarding Type STEL TWA ational exposure to chemical ag Type STEL TWA vorkers from exposure to chemic Type STEL TWA overnment of the Slovak Repub Type TWA Limits	Maximum Allowable Concent Value 10 mg/m3 5 mg/m3 gents (NP 1796) Value 10 mg/m3 5 mg/m3 cal agents at the workplace Value 10 mg/m3 5 mg/m3 stic concerning protection of I Value 1 mg/m3 5 mg/m3	The and mist.

Sweden. Occupational Exposure Limit Values

Components	Туре		Value	Form
Lubricating oils (CAS 74869-22-0)	STEL		3 mg/m3	Mist.
	TWA		1 mg/m3	Mist.
Biological limit values	No biological exposure	limits noted for the ingre	edient(s).	
Recommended monitoring procedures	Follow standard monito	ring procedures.		
Derived no-effect level (DNEL)	Not available.			
Predicted no effect concentration	ons (PNECs)			
Components	Туре	Route	Value	Form
Lubricating oils (CAS 74869-2	22-0) Oral	Oral	9,33 mg/kg	
8.2. Exposure controls				
Appropriate engineering controls	Provide adequate venti inhalation of vapours a		onal exposure limit	s and minimise the risk of
ndividual protection measures,	such as personal prote	ctive equipment		
General information	Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.			
Eye/face protection	Risk of splashes: Wear	approved safety goggle	s.	
Skin protection				
- Hand protection	Wear protective gloves. Be aware that the liquid may penetrate the gloves. Frequent change is advisable.			
- Other	Wear appropriate clothing to prevent repeated or prolonged skin contact.			
Respiratory protection	In case of inadequate ventilation or risk of inhalation of oil mist, suitable respiratory equipment with combination filter (type A2/P2) can be used.			
Thermal hazards	When material is heated, wear gloves to protect against thermal burns.			
Hygiene measures		king, and/or smoking. Re		g after handling the material clothing and protective
Environmental exposure controls	Environmental manage	r must be informed of al	ll major spillages.	

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	
Physical state	Liquid.
Form	Liquid.
Colour	Yellow.
Odour	Slight.
Odour threshold	Not available.
рН	Not applicable.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	236 °C (456,8 °F) Cleveland open cup
Evaporation rate	Not available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or exp	losive limits
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	0,86 (15 °C)
Solubility(ies)	Insoluble in water.

Yamalube 15w-50 Performance (For MC) 913292 Version No.: 01 Revision date: - Issue date: 22-March-2013

Partition coefficient	Not available.
(n-octanol/water)	
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Explosive properties	Not available.
Oxidizing properties	Not available.
9.2. Other information	
Pour point	-40 °C (-40 °F)

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Stable at normal conditions.
10.3. Possibility of hazardous reactions	Will not occur.
10.4. Conditions to avoid	Heat, sparks, flames. High temperatures.
10.5. Incompatible materials	Halogens. Strong acids. Alkalies. Acidifying substances. Strong oxidising agents.
10.6. Hazardous decomposition products	Carbon monoxide.

SECTION 11: Toxicological information

General information

Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure			
Ingestion	May cause discomfort if swalle	wed.	
Inhalation	In high concentrations, vapour nausea.	s are narcotic and may cause headache, fatigue, dizziness and	
Skin contact	Prolonged or repeated contact	with used oil may cause serious skin diseases, such as dermatitis.	
Eye contact	Direct contact with eyes may c	ause temporary irritation.	
Symptoms	Dermatitis.		
11.1. Information on toxicological effects			
Acute toxicity	May cause discomfort if swalle	wed.	
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.		
Serious eye damage/irritation	May cause eye irritation.		
Respiratory sensitisation	No data available.		
Skin sensitisation	No data available.		
Germ cell mutagenicity	No data available.		
Carcinogenicity	This product is not considered	to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
IARC Monographs. Overall Evaluation of Carcinogenicity			
Lubricating oils (CAS 748	69-22-0)	3 Not classifiable as to carcinogenicity to humans.	
Reproductive toxicity	No data available.		
Specific target organ toxicity - single exposure	No data available.		
Specific target organ toxicity - repeated exposure	No data available.		
Aspiration hazard	No data available.		
Mixture versus substance information	Not available.		
Other information	The harmful effects may increa	ase in used oil.	
SECTION 12: Ecological information			
12.1. Toxicity	Harmful to aquatic life with lon	g lasting effects.	
12.2. Persistence and degradability	No data available.		
12.3. Bioaccumulative potential	No data available.		
Partition coefficient n-octanol/water (log Kow)	Not available.		

Yamalube 15w-50 Performance (For MC) 913292 Version No.: 01 Revision date: - Issue date: 22-March-2013

Bioconcentration factor (BCF)	Not available.
12.4. Mobility in soil	Not available.
Mobility in general	The product is insoluble in water and will spread on the water surface.
12.5. Results of PBT and vPvB assessment	Not a PBT or vPvB substance or mixture.
12.6. Other adverse effects	Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste	Dispose of in accordance with local regulations. Do not discharge into drains, water courses or onto the ground.
Contaminated packaging	Since emptied containers retain product residue, follow label warnings even after container is emptied.
EU waste code	13 02 05* The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

SECTION 14: Transport information

ADR

The product is not covered by international regulation on the transport of dangerous goods. **RID**

The product is not covered by international regulation on the transport of dangerous goods.

ADN

The product is not covered by international regulation on the transport of dangerous goods.

IATA

The product is not covered by international regulation on the transport of dangerous goods.

IMDG

The product is not covered by international regulation on the transport of dangerous goods.

14.7. Transport in bulk This substance/mixture is not intended to be transported in bulk.

according to Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I Not listed.

- Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex II Not listed.
- Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended Not listed.
- Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 1 as amended Not listed.
- Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 2 as amended Not listed.
- Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 3 as amended Not listed.
- Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry

Not listed.

Regulation (EC) No. 1907/2006, REACH Article 59(1) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 143/2011 Annex XIV Substances Subject to Authorisation
Not listed

Restrictions on use

Yamalube 15w-50 Performance (For MC) 913292 Version No.: 01 Revision date: - Issue date: 22-March-2013

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Lubricating oils (CAS 74869-22-0) Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work Not regulated. Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding Lubricating oils (CAS 74869-22-0) Other EU regulations Directive 96/82/EC (Seveso II) on the control of major-accident hazards involving dangerous substances Not regulated. Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work Lubricating oils (CAS 74869-22-0) Directive 94/33/EC on the protection of young people at work Lubricating oils (CAS 74869-22-0) Other regulations This Safety Data Sheet complies with the requirements of Regulation (EC) No 453/2010. National regulations Follow national regulation for work with chemical agents. 15.2. Chemical safety No Chemical Safety Assessment has been carried out. assessment SECTION 16: Other information List of abbreviations DNEL: Derived No-Effect Level. PNEC: Predicted No-Effect Concentration. PBT: Persistent, bioaccumulative and toxic. vPvB: Very Persistent and very Bioaccumulative. References CONCAWE Information on evaluation The mixture is classified based on test data for physical hazards. The classification for health and method leading to the environmental hazards is derived by a combination of calculation methods and test data, if available. For details, refer to Sections 9, 11 and 12. classification of mixture Full text of any statements or R38 Irritating to skin. **R-phrases and H-statements** R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. under Sections 2 to 15 R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. H315 - Causes skin irritation. H400 - Very toxic to aquatic life. H410 - Very toxic to aquatic life with long lasting effects. **Training information** Follow training instructions when handling this material.

Disclaimer

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.